

# Package: bindr (via r-universe)

August 30, 2024

**Title** Parametrized Active Bindings

**Version** 0.1.1.9000

**Description** Provides a simple interface for creating active bindings where the bound function accepts additional arguments.

**Suggests** testthat

**LazyData** true

**Date** 2018-03-13

**BugReports** <https://github.com/krlmlr/bindr/issues>

**URL** <https://github.com/krlmlr/bindr>, <https://krlmlr.github.io/bindr>

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.3.2.9000

**License** MIT + file LICENSE

**Encoding** UTF-8

**Repository** <https://krlmlr.r-universe.dev>

**RemoteUrl** <https://github.com/krlmlr/bindr>

**RemoteRef** HEAD

**RemoteSha** 6cf14256e24628fcee2701fe8d579ffa627aa5b4

## Contents

bindr-package . . . . .	2
create_env . . . . .	2

<b>Index</b>	<b>4</b>
--------------	----------

---

bindr-package

*bindr: Parametrized Active Bindings*

---

## Description

Provides a simple interface for creating active bindings where the bound function accepts additional arguments.

## Details

See `create_env()` for creating an environment populated with active bindings, and `populate_env()` for populating an existing environment.

## Author(s)

**Maintainer:** Kirill Müller <krlmlr+r@mailbox.org> ([ORCID](#))

Other contributors:

- RStudio [copyright holder, funder]

## See Also

Useful links:

- <https://github.com/krlmlr/bindr>
- <https://krlmlr.github.io/bindr>
- Report bugs at <https://github.com/krlmlr/bindr/issues>

---

create\_env

*Create or populate an environment with parametrized active bindings*

---

## Description

Leverages `makeActiveBinding()` by allowing parametrized functions that take the name of the binding and an arbitrary number of additional arguments.

## Usage

```
create_env(names, fun, ..., .envir = parent.frame(), .enclos = parent.frame())
```

```
populate_env(env, names, fun, ..., .envir = parent.frame())
```

**Arguments**

names	A <b>name</b> , or a list of names, or a character vector; in the latter case the names are mangled if they are not representable in the native encoding
fun	A <b>function</b> with at least one argument, which will be called to compute the value of a binding. The function will be called with the binding name as first argument (unnamed), and ... as additional arguments
...	Additional arguments to fun
.envir	The <b>environment</b> in which fun will be executed, important if fun calls other functions that are not globally visible
.enclos	The enclosing environment (parent .env) for the newly created environment
env	An environment

**Examples**

```
env <- create_env(letters, paste0, "-lowercase")
env$a
env$c
env$Z
populate_env(env, LETTERS, paste0, "-uppercase")
env$a
env$Z
```

# Index

`bindr` (`bindr`-package), 2  
`bindr`-package, 2

`create_env`, 2  
`create_env()`, 2

environment, 3

function, 3

`makeActiveBinding()`, 2

name, 3

`populate_env` (`create_env`), 2  
`populate_env()`, 2